



MSDS - Diamond Glass NANO Sealer

SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT ID -----: 35-DGNS100/500/5500
PRODUCT CLASS -----: SEALER
TRADE NAME -----: Engineered Nano Sealer (ENS)
FORMULA ID -----: 9908W0.000.250
MSDS PREPARATION DATE ---: 02/02/2010

MANUFACTURER IDENTIFICATION:

NAME -----: Universal Polishing Systems
ADDRESS -----: 4333 Silver Star Rd. – Suite 175
Orlando, FL 32808
TELEPHONE -----: 888-877-4899
EMERGENCY CONTACT ---:
EMERGENCY TELEPHONE-: 516-819-3004

SECTION 2 – COMPOSITION / INFORMATION ON HAZARDOUS MATERIAL

SECTION 3 – HAZARDOUS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES : Exposure to liquid may cause mild eye irritation. Symptoms may include stinging, tearing and redness.

SKIN : May cause skin defatting with prolonged exposure. Exposure may cause skin irritation. Prolonged or repeated exposure may dry the skin.

INHALATION : Causes mild respiratory irritation. Breathing large amounts may be harmful. Symptoms of exposure may include irritation (nose, throat, respiratory tract) and CNS depression.

INGESTION : Swallowing small amounts of this product during normal handling is not likely to cause harmful effects, but swallowing large amounts may be harmful.

CHRONIC EFFECTS

NOTICE : Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause respiratory and/or skin sensitization.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Any pre-existing respiratory or eye/skin conditions

POSSIBLE ROUTES OF ENTRY

Inhalation, ingestion, skin absorption

CARCINOGENICITY

SECTION 4 – FIRST AID MEASURES

EMERGENCY FIRST AID:

EYE CONTACT : If irritation or redness develops, move victim away from exposure and into fresh air. Flush eyes with clean water, holding eyelids apart. If symptoms persist, seek medical attention.

SKIN CONTACT: Remove contaminated shoes and clothing, and flush affected area with large amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. If skin surface is not damaged, cleanse affected area thoroughly by washing with mild soap and water. If irritation or redness develops, seek medical attention. Launder clothing before reuse.

INHALATION: If respiratory symptoms develops, move victim away from source of exposure and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention. Keep person warm and quiet.

INGESTION: Aspiration hazard. Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. If the victim is drowsy or unconscious, place on left side with head down. If possible, do not leave victim unattended. Seek immediate medical attention.

SECTION 5 – FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

Flammability Classification ----- Non Regulated

Flashpoint -----200C

Explosive Limits-----Lower --- 1.2 Upper --- 23.5

EXTINGUISHING MEDIA : Use National Fire Protection Association (NFPA) Class B extinguisher (carbon dioxide, dry chemical or foam)

FIRE FIGHTING INSTRUCTIONS: During fire, a water spray can scatter flames and should be used by experienced firefighters. Firefighters should wear self-contained breathing apparatus with full face piece operated in the positive pressure mode when fighting fires. Isolate damage area, keep unauthorized personnel out. Avoid spreading burning liquid with water used for cooling purposes.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible liquid. Forms combustible mixtures with air at or above the flash point. This product can accumulate static charges, which

can cause fire or explosion. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition source where they may ignite or explode and flash back.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate all ignition sources. Spilled material may be absorbed into an appropriate absorbent material. Prevent spilled material from entering sewers, storm drains and other authorized treatment drainage systems and natural waterways. Stop spill/release if it can be done, and stay away from spill. Isolate danger and keep unauthorized personnel out. Use non-sparking tools and explosion-proof equipment.

CLEAN-UP: warn occupants in surrounding and downwind areas of fire and explosion hazard to stay clear. Remove from surface with suitable absorbents. If allowed by local authorities, sinking and /or suitable dispersants may be used in non-confined waters.

SECTION 7 – HANDLING AND STORAGE

HANDLING: Keep container closed. Handle and open container with care. Open container slowly to relieve any pressure. DO NOT cut, weld or puncture on or near container.

STORAGE: Keep container (s) tightly closed. Use and store this product in a cool, dry, well ventilated area away from heat, direct sunlight, hot metal material. Protect container (s) against physical damage

WARNING: Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperatures and pressures, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources.

SECTION 8 – EXPOSURE CONTROLS, PERSONAL PROTECTION

VENTILATION: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV (s)

RESPIRATORY PROTECTION: If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor / particulate respirator approved by NIOSH for protection against chemicals in section (2 &/or 15).

EYE PROTECTION: Wear safety glasses or goggles to protect against exposure. Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other types of safety glasses.

PROTECTIVE GLOVES: Appropriate disposable gloves are acceptable, such as , nitrile rubber gloves.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	LIQUID
VAPOR PRESSURE:	
VAPOR DENSITY:	HEAVIER THAN AIR
BOILING POINT RANGE:	LOWER – 212.0 F HIGHER – 446.0F
SPECIFIC GRAVITY:	1.095
WEIGHT per VOLUME:	9.12 LB/GL
VOC – TOTAL (lbs./gal):	0.38 LBS/GAL MINUS WATER, 0.08 LBS/GAL AS RECEIVED
EVAPORATION RATE:	0.02
VOLATILE BY WEIGHT:	71.29%
VOLATILE BY VOLUME:	77.08%

SECTION 10 – STABILITY AND REACTIVITY

STABILITY: This product is stable

INCOMPATIBILITIES: (Materials to avoid): This product can react violently with strong oxidizing agents such as chlorine, oxygen, or strong oxidizing acids, such as nitric and sulfuric.

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: Avoid heat, sparks, open flames and other sources of ignition

HAZARDOUS PRODUCTS OF DECOMPOSITION: Heating to decomposition, as in a fire or welding, may produce hazardous fumes. Fumes may contain carbon monoxide and oxides of nitrogen.

SECTION 11 – TOXICOLOGICAL INFORMATION

NO DATA AT THIS TIME

SECTION 12 – ECOLOGICAL INFORMATION

NO DATA AT THIS TIME

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of this product in accordance with applicable local, county, state and federal regulations, by incinerating, or treating and disposing in approved facility. Do not incinerate closed containers.

SECTION 14 – TRANSPORT INFORMATION

DOT HAZARD CLASS: NOT REGULATED
DOT PACKAGING GROUP: PG III
DOT LABEL: NON REGULATED
DOT SHIPPING NAME: PAINT
DOT PLACARD: NON REGULATED
UN/NA NUMBER:

SECTION 15 – REGULATORY INFORMATION

U.S FEDERAL REGULATION INFORMATION

TSCA SECTION 8 (b) – INVENTORY STATUS: All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SECTION 16 – OTHER INFORMATION

Prepared by:
Date of issue: 7/2/2009
Last Revision Date: 02/02/2010
MSDS Prepared for: 9908W0.000.250
MSDS Last Prepared: None
HMIS Rating: Health: 1 Flammability: 0 Reactivity: 0

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200 (g) (4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product ,may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied and assume no liability in connection with any use of this information

Abbreviations used: int. – interior; ext. – exterior; MSDS – Material Safety Data Sheet; HMIS – Hazardous Materials Information Systems; CAS –Chemical Abstracts Services; pct – percent; wt – weight; mm Hg- millimeters of mercury; F- Fahrenheit; ACGIH- American Conference of Governmental Industrial Hygienists; TLV- Threshold Limit Value; OSHA- Occupational Safety and Health Administration; PEL – Permissible Exposure Limit; TWA – Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable; IARC- International Agency for Research on Cancer; NE- Not established; NTP- national Toxicological Program; CFR- Code of Federal Regulations; OSHA- Z 29 CFR 1910, subpart Z; VOC- Volatile Organic Compounds; TCC- Tag Closed Cup; LEL- Lower Explosive Limit; Mg/M³ or Mg/Cu M –milligram per cubic meter; mppcf – millions of particles per cubic foot; ppm- parts per million; NIOSH- National Institute of Occupational Safety and Health; MSHA- Mine Safety and Health Administration; CNS- Central Nervous System