

## Series 37 – PCD with Bar Tooling

### Technical Data:

#### Packaging

9 per box

#### Coverage

Coverage can vary from surface to surface depending on roughness, porosity and density of the medium being applied. Application technique can also vary the coverage. On flat, dense surfaces, the coverage should generally range from 5,000 to 10,000 square feet per set. Wet grinding will usually extend the life of the tooling.

#### Specifications

Bond Color:

N/A

Grit/Velcro Color:

N/A

Bond Matrix:

Hard Bond

Size Available:

3" x 2" Trapezoid

Thickness:

3/16" to 1/4"

Maximum Speed: 1000

RPM

Use **WET** or **DRY**

©Copyright 2012

All rights reserved

### Description

**The 37 Series PCD with Bar** tooling has two offset 3/8" wide PCD diamonds with an angled 30 grit Hard Bond Metal Bar. The Polycrystalline Diamonds (PCD) are very heat and fracture resistant, making them a great coating removal tool.

### Uses

**The 37 Series PCD with Bar** tooling is designed with the 30 grit bar to prevent the deeper scratching and gouging while still aggressively removing the coatings. It is generally the PCD of choice during prep for a final polished floor or stained and sealed floor.

### Application

**The 37 Series PCD with Bar** tooling is the fastest way to remove coatings over 2 mils in thickness without harsh chemicals or messy shot blasting. Both PCD's (Double and Single Bar) stand up well to high heat and are fracture resistant.



37 Series – PCD with Bar